

Package: dggridR (via r-universe)

June 12, 2024

Type Package

Title Discrete Global Grids

Version 3.1.0

Date 2023-07-10

Author Richard Barnes [aut, cre], Kevin Sahr [aut, cph], Gerald Evenden [cph], Angus Johnson [cph], Frank Warmerdam [cph], Even Rouault [cph], Lian Song [ctb], Sebastian Krantz [ctb]

Maintainer Richard Barnes <rijard.barnes@gmail.com>

NeedsCompilation yes

Depends R (>= 3.4.0)

Imports Rcpp (>= 0.12.12), collapse (>= 1.8.0), sf (>= 1.0), s2 (>= 1.1)

LinkingTo Rcpp

RcppModules dgfuncs, gridgens, gridstats

Suggests ggplot2, dplyr, knitr, rmarkdown, maps, mapproj, R.rsp, testthat

License AGPL (>= 3)

Description Spatial analyses involving binning require that every bin have the same area, but this is impossible using a rectangular grid laid over the Earth or over any projection of the Earth. Discrete global grids use hexagons, triangles, and diamonds to overcome this issue, overlaying the Earth with equally-sized bins. This package provides utilities for working with discrete global grids, along with utilities to aid in plotting such data.

URL <https://github.com/r-barnes/dggridR/>

BugReports <https://github.com/r-barnes/dggridR/>

RoxygenNote 7.2.3

Encoding UTF-8

VignetteBuilder knitr, R.rsp

SystemRequirements C++11

Language en-US

Repository <https://fastverse.r-universe.dev>

RemoteUrl <https://github.com/SebKrantz/dggridR>

RemoteRef HEAD

RemoteSha f5bb0dfdafcb1ef89469eb296c722aeb6565a314

Contents

dgcellstogrid	3
dgconstruct	4
dgearthgrid	5
dgGEO_to_GEO	6
dgGEO_to_PLANE	7
dgGEO_to_PROJTRI	8
dgGEO_to_Q2DD	8
dgGEO_to_Q2DI	9
dgGEO_to_SEQNUM	10
dggetres	11
dginfo	11
dgmaxcell	12
dgPROJTRI_to_GEO	13
dgPROJTRI_to_PLANE	13
dgPROJTRI_to_PROJTRI	14
dgPROJTRI_to_Q2DD	15
dgPROJTRI_to_Q2DI	16
dgPROJTRI_to_SEQNUM	16
dgQ2DD_to_GEO	17
dgQ2DD_to_PLANE	18
dgQ2DD_to_PROJTRI	19
dgQ2DD_to_Q2DD	19
dgQ2DD_to_Q2DI	20
dgQ2DD_to_SEQNUM	21
dgQ2DI_to_GEO	22
dgQ2DI_to_PLANE	22
dgQ2DI_to_PROJTRI	23
dgQ2DI_to_Q2DD	24
dgQ2DI_to_Q2DI	25
dgQ2DI_to_SEQNUM	25
dgquakes	26
dgrectgrid	27
dgsavegrid	28
dgSEQNUM_to_GEO	28
dgSEQNUM_to_PLANE	29
dgSEQNUM_to_PROJTRI	30
dgSEQNUM_to_Q2DD	30

dgSEQNUM_to_Q2DI	31
dgSEQNUM_to_SEQNUM	32
dgsetres	32
dgshptogrid	33
dgverify	34
dg_closest_res	35
dg_closest_res_to_area	36
dg_closest_res_to_cls	37
dg_closest_res_to_spacing	38
dg_env	39
dg_process_polydata	39
dg_shpname_south_africa	40

Index **41**

dgcellstogrid *Return boundary coordinates for specified cells*

Description

Returns the coordinates constituting the boundary of a specified set of cells. Duplicates are eliminated to reduce processing and storage requirements.

Usage

```
dgcellstogrid(dggs, cells, savegrid = NA, return_sf = TRUE)
```

Arguments

dggs	A dggs object from dgconstruct()
cells	The cells to get the boundaries of
savegrid	If savegrid is set to a file path, then a shapefile containing the grid is written to that path and the filename is returned. No other manipulations are done. Default: NA (do not save grid, return it)
return_sf	logical. If FALSE, a long-format data frame giving the coordinates of the vertices of each cell is returned. This is considerably faster and more memory efficient than creating an sf data frame.

Value

Returns an sf object. If !is.na(savegrid), returns a filename.

Examples

```

library(dggridR)
data(dgquakes)

#Construct a grid with cells about ~1000 miles wide
dggs      <- dgconstruct(spacing=1000,metric=FALSE)
dgquakes$cell <- dgGEO_to_SEQNUM(dggs,dgquakes$lat,dgquakes$lon)$seqnum

#Get grid cells for the earthquakes identified
grid      <- dgcellstogrid(dggs, dgquakes$cell)

```

dgconstruct	<i>Construct a discrete global grid system (dggs) object</i>
-------------	--

Description

Construct a discrete global grid system (dggs) object

Usage

```

dgconstruct(
  projection = "ISEA",
  aperture = 3,
  topology = "HEXAGON",
  res = NA,
  precision = 7,
  area = NA,
  spacing = NA,
  cls = NA,
  resround = "nearest",
  metric = TRUE,
  show_info = TRUE,
  azimuth_deg = 0,
  pole_lat_deg = 58.28252559,
  pole_lon_deg = 11.25
)

```

Arguments

projection	Type of grid to use. Options are: ISEA and FULLER. Default: ISEA3H
aperture	How finely subsequent resolution levels divide the grid. Options are: 3, 4. Not all options work with all projections and topologies. Default: 3
topology	Shape of cell. Options are: HEXAGON, DIAMOND, TRIANGLE. Default: HEXAGON

res	Resolution. Must be in the range [0,30]. Larger values represent finer resolutions. Appropriate resolutions can be found with <code>dg_closest_res_to_area()</code> , <code>dg_closest_res_to_spacing()</code> , and <code>dg_closest_res_to_cls()</code> . Default is 9, which corresponds to a cell area of ~2600 sq km and a cell spacing of ~50 km. Only one of res, area, length, or cls should be used.
precision	Round output to this number of decimal places. Must be in the range [0,30]. Default: 7.
area	The desired area of the grid's cells. Only one of res, area, length, or cls should be used.
spacing	The desired spacing between the center of adjacent cells. Only one of res, area, length, or cls should be used.
cls	The desired CLS of the cells. Only one of res, area, length, or cls should be used.
resround	What direction to search in. Must be nearest, up, or down.
metric	Whether input and output should be in metric (TRUE) or imperial (FALSE)
show_info	Print the area, spacing, and CLS of the chosen resolution.
azimuth_deg	Rotation in degrees of grid about its pole, value in [0,360]. Default=0.
pole_lat_deg	Latitude in degrees of the pole, value in [-90,90]. Default=58.28252559.
pole_lon_deg	Longitude in degrees of the pole, value in [-180,180]. Default=11.25.

Value

Returns a `dggs` object which can be passed to other `dggridR` functions

Examples

```
library(dggridR)
dggs <- dgconstruct(res=20)

dggs <- dgconstruct(area=5,metric=FALSE)
```

<code>dgearthgrid</code>	<i>Return the coordinates constituting the boundary of cells for the entire Earth</i>
--------------------------	---

Description

Note: If you have a high-resolution grid this may take a very long time to execute.

Usage

```
dgearthgrid(dggs, savegrid = NA, return_sf = TRUE)
```

Arguments

dggs	A dggs object from dgconstruct().
savegrid	If savegrid is set to a file path, then a shapefile containing the grid is written to that path and the filename is returned. No other manipulations are done. Default: NA (do not save grid, return it)
return_sf	logical. If FALSE, a long-format data frame giving the coordinates of the vertices of each cell is returned. This is considerably faster and more memory efficient than creating an sf data frame.

Value

Returns an sf object. If `!is.na(savegrid)`, returns a filename.

Examples

```
library(dggridR)
dggs <- dgconstruct(res=20)
res <- dg_closest_res_to_spacing(dggs, spacing=1000, round='down', metric=FALSE)
dggs <- dgsetres(dggs, res)
gridfilename <- dgearthgrid(dggs, savegrid=tempfile(fileext=".shp")) #Save directly to a file
```

 dgGEO_to_GEO

Convert from GEO to GEO

Description

Uses a discrete global grid system to convert between GEO and GEO (see vignette for details)

Usage

```
dgGEO_to_GEO(dggs, in_lon_deg, in_lat_deg)
```

Arguments

dggs	A dggs object from dgconstruct()
in_lon_deg	Vector of longitude, in degrees
in_lat_deg	Vector of latitude, in degrees

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgGEO_to_GEO(dggs, in_lon_deg, in_lat_deg)  
  
## End(Not run)
```

dgGEO_to_PLANE	<i>Convert from GEO to PLANE</i>
----------------	----------------------------------

Description

Uses a discrete global grid system to convert between GEO and PLANE (see vignette for details)

Usage

```
dgGEO_to_PLANE(dggs, in_lon_deg, in_lat_deg)
```

Arguments

dggs	A dggs object from dgconstruct()
in_lon_deg	Vector of longitude, in degrees
in_lat_deg	Vector of latitude, in degrees

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgGEO_to_PLANE(dggs, in_lon_deg, in_lat_deg)  
  
## End(Not run)
```

dgGEO_to_PROJTRI *Convert from GEO to PROJTRI*

Description

Uses a discrete global grid system to convert between GEO and PROJTRI (see vignette for details)

Usage

```
dgGEO_to_PROJTRI(dggs, in_lon_deg, in_lat_deg)
```

Arguments

dggs	A dggs object from dgconstruct()
in_lon_deg	Vector of longitude, in degrees
in_lat_deg	Vector of latitude, in degrees

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgGEO_to_PROJTRI(dggs, in_lon_deg, in_lat_deg)

## End(Not run)
```

dgGEO_to_Q2DD *Convert from GEO to Q2DD*

Description

Uses a discrete global grid system to convert between GEO and Q2DD (see vignette for details)

Usage

```
dgGEO_to_Q2DD(dggs, in_lon_deg, in_lat_deg)
```


Arguments

dggs	A dggs object from dgconstruct()
in_lon_deg	Vector of longitude, in degrees
in_lat_deg	Vector of latitude, in degrees

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgGEO_to_Q2DD(dggs, in_lon_deg, in_lat_deg)  
  
## End(Not run)
```

dgGEO_to_Q2DI	<i>Convert from GEO to Q2DI</i>
---------------	---------------------------------

Description

Uses a discrete global grid system to convert between GEO and Q2DI (see vignette for details)

Usage

```
dgGEO_to_Q2DI(dggs, in_lon_deg, in_lat_deg)
```

Arguments

dggs	A dggs object from dgconstruct()
in_lon_deg	Vector of longitude, in degrees
in_lat_deg	Vector of latitude, in degrees

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgGEO_to_Q2DI(dggs, in_lon_deg, in_lat_deg)  
  
## End(Not run)
```

dgGEO_to_SEQNUM	<i>Convert from GEO to SEQNUM</i>
-----------------	-----------------------------------

Description

Uses a discrete global grid system to convert between GEO and SEQNUM (see vignette for details)

Usage

```
dgGEO_to_SEQNUM(dggs, in_lon_deg, in_lat_deg)
```

Arguments

dggs	A dggs object from dgconstruct()
in_lon_deg	Vector of longitude, in degrees
in_lat_deg	Vector of latitude, in degrees

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgGEO_to_SEQNUM(dggs, in_lon_deg, in_lat_deg)  
  
## End(Not run)
```

`dggetres`*Get table of grid resolution information*

Description

Gets a grid's resolution and cell property info as a data frame.

Usage

```
dggetres(dggs)
```

Arguments

`dggs` A `dggs` object from `dgconstruct()`

Value

A data frame containing the resolution levels, number of cells, area of those cells, intercell spacing, and characteristic length scale of the cells. All values are in kilometres.

Examples

```
library(dggridR)
dggs <- dgconstruct(res=20)
dggetres(dggs)
```

`dginfo`*Print info about a dggs object to the screen*

Description

`dggs` objects have many settings. This returns all of them, along with info about the grid being specified.

Usage

```
dginfo(dggs)
```

Arguments

`dggs` A `dggs` object from `dgconstruct()`

Value

No return. All info is printed to the screen.

Examples

```
library(dggridR)
dggs <- dgconstruct(res=20)
dginfo(dggs)
```

dgmaxcell

Get largest cell id for a dggs

Description

Cells are labeled 1-N. This function returns N. This is useful if you want to choose cells from the dggs randomly.

Usage

```
dgmaxcell(dggs, res = NA)
```

Arguments

dggs	A dggs object from dgconstruct()
res	If NA, use the resolution specified by the dggs. Otherwise, override the resolution.

Value

The maximum cell id.

Examples

```
#Choose a set of cells randomly distributed over the Earth
library(dggridR)
dggs <- dgconstruct(spacing=1000, metric=FALSE, resround='down')
N <- 100 #Number of cells
maxcell <- dgmaxcell(dggs) #Get maximum cell id
cells <- sample(1:maxcell, N, replace=FALSE) #Choose random cells
grid <- dgcellstogrid(dggs,cells) #Get grid
```

dgPROJTRI_to_GEO *Convert from PROJTRI to GEO*

Description

Uses a discrete global grid system to convert between PROJTRI and GEO (see vignette for details)

Usage

```
dgPROJTRI_to_GEO(dggs, in_tnum, in_tx, in_ty)
```

Arguments

dggs	A dggs object from dgconstruct()
in_tnum	Vector of triangle numbers
in_tx	Vector of triangle x values
in_ty	Vector of triangle y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgPROJTRI_to_GEO(dggs, in_tnum, in_tx, in_ty)  
  
## End(Not run)
```

dgPROJTRI_to_PLANE *Convert from PROJTRI to PLANE*

Description

Uses a discrete global grid system to convert between PROJTRI and PLANE (see vignette for details)

Usage

```
dgPROJTRI_to_PLANE(dggs, in_tnum, in_tx, in_ty)
```

Arguments

dggs	A dggs object from dgconstruct()
in_tnum	Vector of triangle numbers
in_tx	Vector of triangle x values
in_ty	Vector of triangle y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgPROJTRI_to_PLANE(dggs, in_tnum, in_tx, in_ty)

## End(Not run)
```

dgPROJTRI_to_PROJTRI *Convert from PROJTRI to PROJTRI*

Description

Uses a discrete global grid system to convert between PROJTRI and PROJTRI (see vignette for details)

Usage

```
dgPROJTRI_to_PROJTRI(dggs, in_tnum, in_tx, in_ty)
```

Arguments

dggs	A dggs object from dgconstruct()
in_tnum	Vector of triangle numbers
in_tx	Vector of triangle x values
in_ty	Vector of triangle y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgPROJTRI_to_PROJTRI(dggs, in_tnum, in_tx, in_ty)

## End(Not run)
```

dgPROJTRI_to_Q2DD *Convert from PROJTRI to Q2DD*

Description

Uses a discrete global grid system to convert between PROJTRI and Q2DD (see vignette for details)

Usage

```
dgPROJTRI_to_Q2DD(dggs, in_tnum, in_tx, in_ty)
```

Arguments

dggs	A dggs object from dgconstruct()
in_tnum	Vector of triangle numbers
in_tx	Vector of triangle x values
in_ty	Vector of triangle y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgPROJTRI_to_Q2DD(dggs, in_tnum, in_tx, in_ty)

## End(Not run)
```

dgPROJTRI_to_Q2DI *Convert from PROJTRI to Q2DI*

Description

Uses a discrete global grid system to convert between PROJTRI and Q2DI (see vignette for details)

Usage

```
dgPROJTRI_to_Q2DI(dggs, in_tnum, in_tx, in_ty)
```

Arguments

dggs	A dggs object from dgconstruct()
in_tnum	Vector of triangle numbers
in_tx	Vector of triangle x values
in_ty	Vector of triangle y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgPROJTRI_to_Q2DI(dggs, in_tnum, in_tx, in_ty)

## End(Not run)
```

dgPROJTRI_to_SEQNUM *Convert from PROJTRI to SEQNUM*

Description

Uses a discrete global grid system to convert between PROJTRI and SEQNUM (see vignette for details)

Usage

```
dgPROJTRI_to_SEQNUM(dggs, in_tnum, in_tx, in_ty)
```


Arguments

dggs	A dggs object from dgconstruct()
in_tnum	Vector of triangle numbers
in_tx	Vector of triangle x values
in_ty	Vector of triangle y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgPROJTRI_to_SEQNUM(dggs, in_tnum, in_tx, in_ty)

## End(Not run)
```

dgQ2DD_to_GEO *Convert from Q2DD to GEO*

Description

Uses a discrete global grid system to convert between Q2DD and GEO (see vignette for details)

Usage

```
dgQ2DD_to_GEO(dggs, in_quad, in_qx, in_qy)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_qx	Vector of quadrant x values
in_qy	Vector of quadrant y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgQ2DD_to_GEO(dggs, in_quad, in_qx, in_qy)  
  
## End(Not run)
```

dgQ2DD_to_PLANE	<i>Convert from Q2DD to PLANE</i>
-----------------	-----------------------------------

Description

Uses a discrete global grid system to convert between Q2DD and PLANE (see vignette for details)

Usage

```
dgQ2DD_to_PLANE(dggs, in_quad, in_qx, in_qy)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_qx	Vector of quadrant x values
in_qy	Vector of quadrant y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgQ2DD_to_PLANE(dggs, in_quad, in_qx, in_qy)  
  
## End(Not run)
```

dgQ2DD_to_PROJTRI *Convert from Q2DD to PROJTRI*

Description

Uses a discrete global grid system to convert between Q2DD and PROJTRI (see vignette for details)

Usage

```
dgQ2DD_to_PROJTRI(dggs, in_quad, in_qx, in_qy)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_qx	Vector of quadrant x values
in_qy	Vector of quadrant y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgQ2DD_to_PROJTRI(dggs, in_quad, in_qx, in_qy)  
  
## End(Not run)
```

dgQ2DD_to_Q2DD *Convert from Q2DD to Q2DD*

Description

Uses a discrete global grid system to convert between Q2DD and Q2DD (see vignette for details)

Usage

```
dgQ2DD_to_Q2DD(dggs, in_quad, in_qx, in_qy)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_qx	Vector of quadrant x values
in_qy	Vector of quadrant y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgQ2DD_to_Q2DD(dggs, in_quad, in_qx, in_qy)

## End(Not run)
```

dgQ2DD_to_Q2DI *Convert from Q2DD to Q2DI*

Description

Uses a discrete global grid system to convert between Q2DD and Q2DI (see vignette for details)

Usage

```
dgQ2DD_to_Q2DI(dggs, in_quad, in_qx, in_qy)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_qx	Vector of quadrant x values
in_qy	Vector of quadrant y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgQ2DD_to_Q2DI(dggs, in_quad, in_qx, in_qy)

## End(Not run)
```

dgQ2DD_to_SEQNUM	<i>Convert from Q2DD to SEQNUM</i>
------------------	------------------------------------

Description

Uses a discrete global grid system to convert between Q2DD and SEQNUM (see vignette for details)

Usage

```
dgQ2DD_to_SEQNUM(dggs, in_quad, in_qx, in_qy)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_qx	Vector of quadrant x values
in_qy	Vector of quadrant y values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgQ2DD_to_SEQNUM(dggs, in_quad, in_qx, in_qy)

## End(Not run)
```

dgQ2DI_to_GEO *Convert from Q2DI to GEO*

Description

Uses a discrete global grid system to convert between Q2DI and GEO (see vignette for details)

Usage

```
dgQ2DI_to_GEO(dggs, in_quad, in_i, in_j)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_i	Vector of quadrant i values
in_j	Vector of quadrant j values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgQ2DI_to_GEO(dggs, in_quad, in_i, in_j)

## End(Not run)
```

dgQ2DI_to_PLANE *Convert from Q2DI to PLANE*

Description

Uses a discrete global grid system to convert between Q2DI and PLANE (see vignette for details)

Usage

```
dgQ2DI_to_PLANE(dggs, in_quad, in_i, in_j)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_i	Vector of quadrant i values
in_j	Vector of quadrant j values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgQ2DI_to_PLANE(dggs, in_quad, in_i, in_j)  
  
## End(Not run)
```

dgQ2DI_to_PROJTRI *Convert from Q2DI to PROJTRI*

Description

Uses a discrete global grid system to convert between Q2DI and PROJTRI (see vignette for details)

Usage

```
dgQ2DI_to_PROJTRI(dggs, in_quad, in_i, in_j)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_i	Vector of quadrant i values
in_j	Vector of quadrant j values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgQ2DI_to_PROJTRI(dggs, in_quad, in_i, in_j)

## End(Not run)
```

dgQ2DI_to_Q2DD	<i>Convert from Q2DI to Q2DD</i>
----------------	----------------------------------

Description

Uses a discrete global grid system to convert between Q2DI and Q2DD (see vignette for details)

Usage

```
dgQ2DI_to_Q2DD(dggs, in_quad, in_i, in_j)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_i	Vector of quadrant i values
in_j	Vector of quadrant j values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgQ2DI_to_Q2DD(dggs, in_quad, in_i, in_j)

## End(Not run)
```

dgQ2DI_to_Q2DI	<i>Convert from Q2DI to Q2DI</i>
----------------	----------------------------------

Description

Uses a discrete global grid system to convert between Q2DI and Q2DI (see vignette for details)

Usage

```
dgQ2DI_to_Q2DI(dggs, in_quad, in_i, in_j)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_i	Vector of quadrant i values
in_j	Vector of quadrant j values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgQ2DI_to_Q2DI(dggs, in_quad, in_i, in_j)  
  
## End(Not run)
```

dgQ2DI_to_SEQNUM	<i>Convert from Q2DI to SEQNUM</i>
------------------	------------------------------------

Description

Uses a discrete global grid system to convert between Q2DI and SEQNUM (see vignette for details)

Usage

```
dgQ2DI_to_SEQNUM(dggs, in_quad, in_i, in_j)
```

Arguments

dggs	A dggs object from dgconstruct()
in_quad	Vector of quad numbers
in_i	Vector of quadrant i values
in_j	Vector of quadrant j values

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgQ2DI_to_SEQNUM(dggs, in_quad, in_i, in_j)

## End(Not run)
```

 dgquakes

All earthquakes with magnitude >=3.0 earthquakes for 2015

Description

A data frame with 19914 observations on the following 4 variables.

time Time of the quake. Example: 2015-12-31T23:39:28.940Z

lat Latitude of the epicenter. Example: -7.0711

lon Longitude of the epicenter. Example: -173.5178

mag Magnitude of the quake. Example: 3.2

Usage

```
data(dgquakes)
```

Format

data frame

Source

The USGS Earthquake Hazards Program (<https://earthquake.usgs.gov/earthquakes/search/>).

dgrectgrid	<i>Return the coordinates constituting the boundary of cells within a specified region</i>
------------	--

Description

Note: This may generate odd results for very large rectangles, because putting rectangles on spheres is weird... as you should know, if you're using this package.

Usage

```
dgrectgrid(
  dggs,
  minlat = -1,
  minlon = -1,
  maxlat = 1,
  maxlon = 1,
  cellsize = 0.1,
  ...
)
```

Arguments

dggs	A dggs object from dgconstruct()
minlat	Minimum latitude of region of interest
minlon	Minimum longitude of region of interest
maxlat	Maximum latitude of region of interest
maxlon	Maximum longitude of region of interest
cellsize	Distance, in degrees, between the sample points used to generate the grid. Small values yield long generation times while large values may omit cells.
...	Further arguments passed to dgcellstogrid .

Value

Returns an sf object. If `!is.na(savegrid)`, returns a filename.

Examples

```
library(dggridR)
dggs <- dgconstruct(spacing=1000,metric=FALSE,resound='down')

#Get grid cells for the conterminous United States
grid <- dgrectgrid(dggs,
  minlat=24.7433195, minlon=-124.7844079,
  maxlat=49.3457868, maxlon=-66.9513812)
```

dgsavegrid	<i>Saves a generated grid to a shapefile</i>
------------	--

Description

Saves a generated grid to a shapefile

Usage

```
dgsavegrid(grid, shpfname)
```

Arguments

grid	Grid to be saved
shpfname	File to save the grid to

Value

The filename the grid was saved to

dgSEQNUM_to_GEO	<i>Convert from SEQNUM to GEO</i>
-----------------	-----------------------------------

Description

Uses a discrete global grid system to convert between SEQNUM and GEO (see vignette for details)

Usage

```
dgSEQNUM_to_GEO(dggs, in_seqnum)
```

Arguments

dggs	A dggs object from dgconstruct()
in_seqnum	Globally unique number identifying the surface polygon

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgSEQNUM_to_GEO(dggs, in_seqnum)  
  
## End(Not run)
```

dgSEQNUM_to_PLANE *Convert from SEQNUM to PLANE*

Description

Uses a discrete global grid system to convert between SEQNUM and PLANE (see vignette for details)

Usage

```
dgSEQNUM_to_PLANE(dggs, in_seqnum)
```

Arguments

dggs	A dggs object from dgconstruct()
in_seqnum	Globally unique number identifying the surface polygon

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgSEQNUM_to_PLANE(dggs, in_seqnum)  
  
## End(Not run)
```

dgSEQNUM_to_PROJTRI *Convert from SEQNUM to PROJTRI*

Description

Uses a discrete global grid system to convert between SEQNUM and PROJTRI (see vignette for details)

Usage

```
dgSEQNUM_to_PROJTRI(dggs, in_seqnum)
```

Arguments

dggs	A dggs object from dgconstruct()
in_seqnum	Globally unique number identifying the surface polygon

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgSEQNUM_to_PROJTRI(dggs, in_seqnum)

## End(Not run)
```

dgSEQNUM_to_Q2DD *Convert from SEQNUM to Q2DD*

Description

Uses a discrete global grid system to convert between SEQNUM and Q2DD (see vignette for details)

Usage

```
dgSEQNUM_to_Q2DD(dggs, in_seqnum)
```

Arguments

dggs A dggs object from dgconstruct()
 in_seqnum Globally unique number identifying the surface polygon

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgSEQNUM_to_Q2DD(dggs, in_seqnum)

## End(Not run)
```

dgSEQNUM_to_Q2DI *Convert from SEQNUM to Q2DI*

Description

Uses a discrete global grid system to convert between SEQNUM and Q2DI (see vignette for details)

Usage

```
dgSEQNUM_to_Q2DI(dggs, in_seqnum)
```

Arguments

dggs A dggs object from dgconstruct()
 in_seqnum Globally unique number identifying the surface polygon

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:
library(dggridR)
dggs <- dgconstruct(res=20)

dgSEQNUM_to_Q2DI(dggs, in_seqnum)

## End(Not run)
```

dgSEQNUM_to_SEQNUM *Convert from SEQNUM to SEQNUM*

Description

Uses a discrete global grid system to convert between SEQNUM and SEQNUM (see vignette for details)

Usage

```
dgSEQNUM_to_SEQNUM(dggs, in_seqnum)
```

Arguments

dggs	A dggs object from dgconstruct()
in_seqnum	Globally unique number identifying the surface polygon

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
## Not run:  
library(dggridR)  
dggs <- dgconstruct(res=20)  
  
dgSEQNUM_to_SEQNUM(dggs, in_seqnum)  
  
## End(Not run)
```

dgsetres *Set the resolution of a dggs object*

Description

Set the resolution of a dggs object

Usage

```
dgsetres(dggs, res)
```


Arguments

dggs	A dggs object from dgconstruct().
res	Resolution. Must be in the range [0,30]. Larger values represent finer resolutions. Appropriate resolutions can be found with dg_closest_res_to_area(), dg_closest_res_to_spacing(), and dg_closest_res_to_cls(). Default is 9, which corresponds to a cell area of ~2600 sq km and a cell spacing of ~50 km. Default: 9.

Value

Returns a dggs object which can be passed to other dggridR functions

Examples

```
library(dggridR)
dggs <- dgconstruct(res=20)
dggs <- dgsetres(dggs,10)
```

dgshptogrid

Return boundary coordinates for cells intersecting a shapefile

Description

Returns the coordinates constituting the boundary of a set of cells which intersect or are contained by a polygon (or polygons) specified in a shapefile. Note that grid cells are also generated for holes in the shapefile's polygon(s).

Note that coordinates in the shapefile must be rounded to check polygon intersections. Currently this round preserves eight decimal digits of precision.

The eighth decimal place is worth up to 1.1 mm of precision: this is good for charting the motions of tectonic plates and the movements of volcanoes. Permanent, corrected, constantly-running GPS base stations might be able to achieve this level of accuracy.

In other words: you should be just fine with this level of precision.

Usage

```
dgshptogrid(dggs, shpfname, cellsize = 0.1, ...)
```

Arguments

dggs	A dggs object from dgconstruct()
shpfname	Either a sf data frame or the file name of the shapefile. Filename should end with '.shp'.
cellsize	Distance, in degrees, between the sample points used to generate the grid. Small values yield long generation times while large values may omit cells.
...	Further arguments passed to dgcellstogrid .

Value

Returns an sf object. If `!is.na(savegrid)`, returns a filename.

Examples

```
## Not run:  
library(dggridR)  
  
dggs <- dgconstruct(spacing=25, metric=FALSE, resound='nearest')  
south_africa_grid <- dgshptogrid(dggs,dg_shpfname_south_africa())  
  
## End(Not run)
```

dgverify

Verify that a dggs object has appropriate values

Description

Verify that a dggs object has appropriate values

Usage

```
dgverify(dggs)
```

Arguments

dggs The dggs object to be verified

Value

The function has no return value. A stop signal is raised if the object is misspecified

Examples

```
library(dggridR)  
dggs <- dgconstruct(res=20)  
dgverify(dggs)
```

dg_closest_res	<i>Determine an appropriate grid resolution based on input data.</i>
----------------	--

Description

This is a generic function that is used to determine an appropriate resolution given an area, cell spacing, or correlated length scale. It does so by extracting the appropriate length/area column and searching it for a value close to the input.

Usage

```
dg_closest_res(  
  dggs,  
  col,  
  val,  
  round = "nearest",  
  show_info = TRUE,  
  metric = TRUE  
)
```

Arguments

dggs	A dggs object from dgconstruct()
col	Column in which to search for a close value. Should be: area_km, spacing_km, or cls_km.
val	The value to search for
round	What direction to search in. Must be nearest, up, or down.
show_info	Print the area, spacing, and CLS of the chosen resolution.
metric	Whether input and output should be in metric (TRUE) or imperial (FALSE)

Value

A number representing the grid resolution

Examples

```
library(dggridR)  
dggs <- dgconstruct(res=20)  
res <- dg_closest_res(dggs, 'area_km', 1)  
dggs <- dgsetres(dggs, res)
```

`dg_closest_res_to_area`*Determine resolution based on desired area*

Description

Determine an appropriate grid resolution based on a desired cell area.

Usage

```
dg_closest_res_to_area(  
  dggs,  
  area,  
  round = "nearest",  
  show_info = TRUE,  
  metric = TRUE  
)
```

Arguments

<code>dggs</code>	A dggs object from <code>dgconstruct()</code>
<code>area</code>	The desired area of the grid's cells
<code>round</code>	What direction to search in. Must be nearest, up, or down.
<code>show_info</code>	Print the area, spacing, and CLS of the chosen resolution.
<code>metric</code>	Whether input and output should be in metric (TRUE) or imperial (FALSE)

Value

A number representing the grid resolution

Examples

```
library(dggridR)  
dggs <- dgconstruct(res=20)  
res <- dg_closest_res_to_area(dggs,1)  
dggs <- dgsetres(dggs,res)
```

dg_closest_res_to_cls *Determine an appropriate grid resolution based on a desired characteristic length scale of the cells.*

Description

The characteristic length scale (CLS) is the diameter of a spherical cap of the same area as a cell of the specified resolution.

Usage

```
dg_closest_res_to_cls(  
  dggs,  
  cls,  
  round = "nearest",  
  show_info = TRUE,  
  metric = TRUE  
)
```

Arguments

dggs	A dggs object from dgconstruct()
cls	The desired CLS of the cells.
round	What direction to search in. Must be nearest, up, or down.
show_info	Print the area, spacing, and CLS of the chosen resolution.
metric	Whether input and output should be in metric (TRUE) or imperial (FALSE)

Value

A number representing the grid resolution

Examples

```
library(dggridR)  
dggs <- dgconstruct(res=20)  
res <- dg_closest_res_to_cls(dggs,1)  
dggs <- dgsetres(dggs,res)
```

`dg_closest_res_to_spacing`*Determine grid resolution from desired spacing.*

Description

Determine an appropriate grid resolution based on a desired spacing between the center of adjacent cells.

Usage

```
dg_closest_res_to_spacing(  
  dggs,  
  spacing,  
  round = "nearest",  
  show_info = TRUE,  
  metric = TRUE  
)
```

Arguments

<code>dggs</code>	A <code>dggs</code> object from <code>dgconstruct()</code>
<code>spacing</code>	The desired spacing between the center of adjacent cells
<code>round</code>	What direction to search in. Must be nearest, up, or down.
<code>show_info</code>	Print the area, spacing, and CLS of the chosen resolution.
<code>metric</code>	Whether input and output should be in metric (TRUE) or imperial (FALSE)

Value

A number representing the grid resolution

Examples

```
library(dggridR)  
dggs <- dgconstruct(res=20)  
res <- dg_closest_res_to_spacing(dggs,1)  
dggs <- dgsetres(dggs,res)
```

`dg_env`*Control global aspects of the dggridR package*

Description

This environment is used to control global features of the dggridR package. At the moment the only option is 'dg_debug' which, when set to TRUE provides extensive outputs useful for tracking down bugs.

Usage`dg_env`**Format**

An object of class environment of length 1.

`dg_process_polydata`*Load a KML file*

Description

Convert data from internal dggrid functions into something useful: an sp object or a data frame

Usage`dg_process_polydata(polydata)`**Arguments**

`polydata` Polygons generated by dggrid. These will be converted.

Value

Returns an sf object.

dg_shpname_south_africa

National border of South Africa

Description

This variable points to a shapefile containing the national border of South Africa

Usage

dg_shpname_south_africa()

Value

A filename of a shapefile containing the national border of South Africa

Index

* datasets

- dg_env, 39
- dgquakes, 26

- dg_closest_res, 35
- dg_closest_res_to_area, 36
- dg_closest_res_to_cls, 37
- dg_closest_res_to_spacing, 38
- dg_env, 39
- dg_process_polydata, 39
- dg_shpfname_south_africa, 40
- dgcellstogrid, 3, 27, 33
- dgconstruct, 4
- dgearthgrid, 5
- dgGEO_to_GEO, 6
- dgGEO_to_PLANE, 7
- dgGEO_to_PROJTRI, 8
- dgGEO_to_Q2DD, 8
- dgGEO_to_Q2DI, 9
- dgGEO_to_SEQNUM, 10
- dggetres, 11
- dginfo, 11
- dgmaxcell, 12
- dgPROJTRI_to_GEO, 13
- dgPROJTRI_to_PLANE, 13
- dgPROJTRI_to_PROJTRI, 14
- dgPROJTRI_to_Q2DD, 15
- dgPROJTRI_to_Q2DI, 16
- dgPROJTRI_to_SEQNUM, 16
- dgQ2DD_to_GEO, 17
- dgQ2DD_to_PLANE, 18
- dgQ2DD_to_PROJTRI, 19
- dgQ2DD_to_Q2DD, 19
- dgQ2DD_to_Q2DI, 20
- dgQ2DD_to_SEQNUM, 21
- dgQ2DI_to_GEO, 22
- dgQ2DI_to_PLANE, 22
- dgQ2DI_to_PROJTRI, 23
- dgQ2DI_to_Q2DD, 24
- dgQ2DI_to_Q2DI, 25

- dgQ2DI_to_SEQNUM, 25
- dgquakes, 26
- dgrectgrid, 27
- dgsavegrid, 28
- dgSEQNUM_to_GEO, 28
- dgSEQNUM_to_PLANE, 29
- dgSEQNUM_to_PROJTRI, 30
- dgSEQNUM_to_Q2DD, 30
- dgSEQNUM_to_Q2DI, 31
- dgSEQNUM_to_SEQNUM, 32
- dgsetres, 32
- dgshptogrid, 33
- dgverify, 34